









	Product	DOF	Materials	Dims	Weight in Air	Weight in Water	Reach	Wrist Travel	Jaw Opening	Working Pressure	Flow	Wrist Torque	Jaw Force	Cutter Dia.	Lift @ Full Ext.	Depth Rating
	HLK-43000	5	316 SS, 6082 Alum, HDPE	Refer to Drawing	8.4kg (18.5lb)	4.2kg (9.24lb)	660mm (26")	180 Deg.	90mm (3.5")	80bar (1160psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	8.2Nm (6lbf.ft)	124N (27.9lbf)	6mm (1/4")	10kg (22lb)	3000msw (9,840ft)
	HLK-4000	5	316 SS, 6082 Alum		12.7kg (28lb)	9.6kg (21.1lb)	860mm (34")	180 Deg.	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	18.7Nm (13.8lbf.ft)	630N (141.6lbf)	19mm (3/4")	25kg (55lb)	6000msw (19,680ft)
	HLK-4200	4	316 SS, 6082 Alum		13.8kg (30lb)	11.2kg (24.6lb)	600mm (23.6")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	40kg (88lb)	6000msw (19,680ft)
	HLK-5600	5	316 SS, 6082 Alum, HDPE		21kg (46lb)	17kg (37lb)	987mm (38.9")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	40kg (88lb)	6000msw (19,680ft)
	HLK-5300	6	316 SS, 6082 Alum, HDPE		36kg (79lb)	20.2kg (44.4lb)	1428mm (56")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	32kg (70lb)	6000msw (19,680ft)
	HLK-50000	4	316 SS, 6082 Alum, HDPE		24.8kg (54.7lb)	16.6kg (36.6lb)	785mm (31")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	80kg (176lb)	6000msw (19,680ft)
	HLK-50010	5	316 SS, 6082 Alum, HDPE		25.2kg (55.4lb)	18.2kg (40lb)	922mm (36")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	80kg (176lb)	6000msw (19,680ft)
	HLK-5680	6	316 SS, 6082 Alum, HDPE		27.8kg (61lb)	21kg (46lb)	1050mm (41.3")	Continuous 360 Degree	154mm (6")	140bar (2000psi)	0.5lpm to 6lpm (0.13gpm to 1.58gpm)	60Nm (44lbf.ft)	690N (155lbf)	19mm (3/4")	40kg (88lb)	6000msw (19,680ft)